

SOPRAGUARD PERIMETER

DESCRIPTION

The Sopraguard Perimeter self-adhesive strip consists of a 15.24 cm (6") wide reinforced EPDM rubber membrane strip, laminated along one edge of the EPDM rubber membrane with a 0.89 mm thick and 7.62 cm (3") wide pressure-sensitive tape.

It is designed for the perimeter fixation of the EPDM rubber membrane without perforating it in ballasted, fully adhered, and mechanically attached roofing systems.



ADVANTAGES

- High resistance to weather, ozone, and UV radiation.
- Eliminates the need for perforation of the waterproof membrane.
- Does not require heat or flame sources for application.
- Provides complete waterproofing continuity at angle changes.

PREPARATION

- The application surface must be clean, dry, and free from aggressive elements or other contaminants that may cause the surface to be uneven and in poor condition.
- Additionally, the surface must be firm, well-bonded, and offer sufficient tensile strength for the anchors.
- The fasteners must be suitable for the type of surface.
- If the product has been exposed to temperatures below 15°C for hours, it must be tempered before application.

APPLICATION INSTRUCTIONS

- Unroll the Sopraguard Perimeter strip with the protective film facing up and the self-adhesive strip away from the angle change.
- When the strip is flat, anchor it to the support with plates and screws (every 300 mm between centers, maximum) either at the base or forming an angle and attaching to the vertical surface.
- If in doubt about its application, consult our technical department.

PRESENTATION, STORAGE AND SHELF LIFE

	SOPRAGUARD PERIMETER
Presentation	Available in rolls 152 mm wide and 30.5 m long.
Storage	Store in its original unopened packaging, in a covered, ventilated area at temperatures between 4° C and 43° C.
Shelf Life	The shelf life is 24 months when stored under the above conditions. Check the manufacturing date on each roll. The actual product expiration depends directly on the storage method and the handling of the accessories. For example, storage at high temperatures can reduce the period of use with optimal results.

PRECAUTIONS

- Do not smoke while in use.
- Professional use only.
- Use in well-ventilated areas.
- Refer to the Safety Data Sheet.

TECHNICAL SPECIFICATIONS

	EPDM MEMBRANE	SELF-ADHESIVE STRIP
Base	Reinforced EPDM	EPDM
Color	Black	Black
Width	15,24 cm	7,62 cm
Length	30,5 m	30,5

	STANDARD	VALUE
Peel resistance on EPDM	ASTM D 413	10 pli @ 70°F (21°C)
Shear resistance on EPDM	ASTM D 816	20 psi @ 70°F (21°C)
Low-temperature fold	ASTM D 746	-50°F (-46°C)

SOPREMA reserves the right to modify the stated data without prior notice and disclaims any liability in case of anomalies caused by improper use of the product.

The values reflected in the technical data sheet correspond to the average values of the tests conducted in our laboratory.

SOPREMA IBERIA SLU c/ Ferro 7, Pol. Ind. Can Pelegrí 08755 Castellbisbal – Barcelona (+34) 93 635 14 00.